



CT3031, CT3032, CT3033

CT3041, CT3042, CT3043

250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Features

- High isolation 5000 VRMS
- Peak Breakdown Voltage
 - 250V – CT3031,3032,3033
 - 400V – CT3041,3042,3043
- Temperature range - 55 °C to 100 °C
- Regulatory Approvals
 - UL - UL1577 (E364000)
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC – GB4943.1, GB8898
 - IEC60065, IEC60950


Applications

- Motor Controls
- Lamp ballasts
- Static AC Power Switch
- Solenoid/ Valve Control


Description

The CT3031, CT3032, CT3033, CT3041, CT3042 and CT3043 consists of a Zero Cross Photo Triac optically coupled to a gallium arsenide Infrared-emitting diode in a 6-Pin DIP package with different lead forming options.

Package Outline



Schematic



Note: Different lead forming options available. See package dimension.



CT3031, CT3032, CT3033

CT3041, CT3042, CT3043

250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Absolute Maximum Rating at 25°C

| Symbol | Parameters | Ratings | Units | Notes |
|-----------------------|--|------------------|------------------|-------|
| V _{ISO} | Isolation voltage | 5000 | V _{RMS} | |
| T _{OPR} | Operating temperature | -55 ~ +100 | °C | |
| T _{STG} | Storage temperature | -55 ~ +150 | °C | |
| T _{SOL} | Soldering temperature | 260 | °C | |
| Emitter | | | | |
| I _F | Forward current | 60 | mA | |
| I _{F(TRANS)} | Peak transient current (≤1μs P.W,300pps) | 1 | A | |
| V _R | Reverse voltage | 6 | V | |
| P _D | Power dissipation | 100 | mW | |
| Detector | | | | |
| P _D | Power dissipation | 300 | mW | |
| V _{DRM} | Off-State Output Terminal Voltage | CT3031,3032,3033 | 250 | V |
| | | CT3041,3042,3043 | 400 | V |
| I _{TSM} | Peak Repetitive Surge Current | 1 | A | |



CT3031, CT3032, CT3033

CT3041, CT3042, CT3043

250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Electrical Characteristics $T_A = 25^\circ\text{C}$ (unless otherwise specified)

Emitter Characteristics

| Symbol | Parameters | Test Conditions | Min | Typ | Max | Units | Notes |
|----------|-------------------|---------------------|-----|-----|-----|---------------|-------|
| V_F | Forward voltage | $I_F = 10\text{mA}$ | - | - | 1.5 | V | |
| I_R | Reverse Current | $V_R = 6\text{V}$ | - | - | 5 | μA | |
| C_{IN} | Input Capacitance | $f = 1\text{MHz}$ | - | 45 | - | pF | |

Detector Characteristics

| Symbol | Parameters | Test Conditions | Min | Typ | Max | Units | Notes |
|------------|---|--|------|-----|-----|------------------------|-------|
| I_{DRM1} | Peak Blocking Current | $I_F = 0\text{mA}$, $V_{DRM} = \text{Rated } V_{DRM}$ | - | - | 100 | nA | |
| I_{DRM2} | Inhibit Leakage Current | $I_F = \text{Rated } I_{FT}$, $V_{DRM} = \text{Rated } V_{DRM}$ | - | - | 500 | μA | |
| V_{INH} | Inhibit Voltage | $I_F = \text{Rated } I_{FT}$ | - | - | 20 | V | |
| V_{TM} | Peak On-State Voltage | $I_F = \text{Rated } I_{FT}$, $I_{TM} = 100\text{mA}$ | - | - | 3 | V | |
| dv/dt | Critical Rate of Rise off-State Voltage | $V_{PEAK} = \text{Rated } V_{DRM}$ | 1000 | - | - | $\text{V}/\mu\text{s}$ | |

Transfer Characteristics

| Symbol | Parameters | Test Conditions | Min | Typ | Max | Units | Notes |
|----------|-----------------------|--|--------------------|------|-----|---------------|-------|
| I_{FT} | Input | Terminal Voltage = 3V $I_{TM} = 100\text{mA}$ | - | - | 15 | mA | |
| | Trigger | | | | 10 | | |
| | Current | | | | 5 | | |
| I_H | Holding Current | | - | 270 | - | μA | |
| R_{IO} | Isolation Resistance | $V_{IO} = 500\text{V}_{DC}$ | 1×10^{11} | - | - | Ω | |
| C_{IO} | Isolation Capacitance | $f = 1\text{MHz}$ | - | 0.25 | - | pF | |



250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Typical Characteristic Curve




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6



250V/400V Zero Cross 6-Pin Phototriac Optocoupler




Figure 7




Figure 8




Figure 9




CT3031, CT3032, CT3033

CT3041, CT3042, CT3043


250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Package Dimension *Dimensions in mm unless otherwise stated*

Standard DIP – Through Hole



Wide Lead Forming – Through Hole (M Type)






CT3031, CT3032, CT3033


CT3041, CT3042, CT3043

250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Surface Mount Forming (S Type)



Surface Mount Forming (Low Profile) (SL Type)






CT3031, CT3032, CT3033


CT3041, CT3042, CT3043

250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Recommended Solder Mask *Dimensions in mm unless otherwise stated*



Marking Information



Note:

- CT : Denotes "CT Micro"
- 3031 : Part Number
- V : VDE Option
- Y : Fiscal Year
- WW : Work Week
- K : Manufacturing Code



CT3031, CT3032, CT3033

CT3041, CT3042, CT3043

250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Ordering Information

CT303X(V)(Y)(Z)-G, CT304X(V)(Y)(Z)-G

X = Part No. (X=1,2,3)

V = VDE Option (V or None)

Y = Lead form option (S, SL, M or none)

Z = Tape and reel option (T1, T2 or none)

G= Material option (G: Green, None: Non-green)

| Option | Description | Quantity |
|---------------|---|-----------------|
| None | Standard 6 Pin Dip | 50Units/Tube |
| M | Gullwing (400mil) Lead Forming | 50Units/Tube |
| S(T1) | Surface Mount Lead Forming – With Option 1 Taping | 1000 Units/Reel |
| S(T2) | Surface Mount Lead Forming – With Option 2 Taping | 1000 Units/Reel |
| SL(T1) | Surface Mount (Low Profile) Lead Forming– With Option 1 Taping | 1000 Units/Reel |
| SL(T2) | Surface Mount (Low Profile) Lead Forming – With Option 2 Taping | 1000 Units/Reel |




CT3031, CT3032, CT3033

CT3041, CT3042, CT3043


250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Carrier Tape Specifications *Dimensions in mm unless otherwise stated*

Option S(T1) & SL(T1)




Option S(T2) & SL(T2)





250V/400V Zero Cross 6-Pin Phototriac Optocoupler

Reflow Profile



| Profile Feature | Pb-Free Assembly Profile |
|-----------------------------------|--------------------------|
| Temperature Min. (Tsmmin) | 150 °C |
| Temperature Max. (Tsmmax) | 200 °C |
| Time (ts) from (Tsmmin to Tsmmax) | 60-120 seconds |
| Ramp-up Rate (tL to tP) | 3 °C/second max. |
| Liquidous Temperature (TL) | 217 °C |
| Time (tL) Maintained Above (TL) | 60 – 150 seconds |
| Peak Body Package Temperature | 260 °C +0 °C / -5 °C |
| Time (tP) within 5 °C of 260 °C | 30 seconds |
| Ramp-down Rate (TP to TL) | 6 °C/second max |
| Time 25 °C to Peak Temperature | 8 minutes max. |



CT3031, CT3032, CT3033

CT3041, CT3042, CT3043

250V/400V Zero Cross 6-Pin Phototriac Optocoupler

DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

DISCOLORATION MIGHT OCCUR ON THE PACKAGE SURFACE AFTER SOLDERING, REFLOW OR LONG TERM USE. THIS DOES NOT IMPACT THE PRODUCT PERFORMANCE NOR THE PRODUCT RELIABILITY.

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*